




Badger Two Ram

For All Materials including OCC, Paper, Plastic, Non-Ferrous Metals, and MSW

Key Advantages:

- Heavy Duty Construction – strongest frame in its class with Hardox 500 replaceable wear liners
- 166 Tons of Compaction force, 16% more than the competitors – leads to heavier bales and less material handling
- 60% Ram penetration – greatly reduces memory in plastics and other materials – compacts on every stroke
- Category III Safety levels – standard
- Hydraulic system with Flooded Suction for long lasting hydraulic components and multiple pump design for added speed when required
- HMI System – 10" touch screen easy to use with multiple operating areas including on the floor as well as elevated on the bale chamber or eject ram
- Best selling Narrow Body 2 ram for 30 years running!



HarrisAmericanCo.com

BADGER TWO RAM



Bale Size: 46" x 31" x 61"
Feed Opening: 65" x 94"
Main Cylinder: 11" bore w/166 tons
Ram Face Pressure 288psi
System Pressure: 3500 psi
Eject Cylinder: 8" bore at 88 tons
Power Saving Soft Start-Standard
Machine Weight: 65,000 pounds

PRODUCTION

	Weights	50-2	75-2	125-2	125-4
OCC	1250-1550	4-6	5-8	10-15	10-15
Plastic	1150-1450	2-3	2-5	2-4	3-7
Paper	1300-1600	6-10	9-12	11-15	17-22
UBC	1000-1200	2-4	3-5	3-7	6-10
NF Metals	1050-2700	3-7	4-8	5-9	7-13
MSW	1900-2400	7-11	10-15	13-22	22-30
Hyd. Tank		400	400	400	600
Production for OCC, Paper, NFM run without Combo Door activated					

PRODUCTION OPTIONS

Hopper Extensions

BobCat Loader Hoppers

Lower Ram Wiper – to protect HiLo floor with scrap metals

Remote Operator Controls



BEYOND THE EXPECTED

HarrisAmericanCo.com • 800-710-4994