



NB Two Ram

For all recycling grades and NF metals

Key Advantages:

- Fabricated from heavy structural members and plate, keyed and fitted for proper alignment. Replaceable liner systems featuring 500 Brinell rating, hardest liners in the two ram class.
- Optimal Hydraulic Operating Pressures – 3000-4000 psi, with ram penetration within 8” of the end wall – 82% - for compaction on every stroke and heavier bales
- Dual Motor Power Unit design – providing you redundancy (if one motor down can still operate), power conservation – one motor can go to sleep mode and automatically be brought back into production on demand.
- Manifold Block System – featuring cartridges instead of poppet valves – much easier to replace as well as the power unit runs much quieter, cooler, and much longer lasting
- HMI with 10” Exor eSmart Touch Screen located on the floor for easy access while running in automatic for most grades.
- Category III Safety – all standard



HarrisAmericanCo.com

NB Two Ram Series

Models: N520, N620
Bale Size: 60" x 30" x 45"
Feed Opening: 74" x 43";
82" x 43" (long side-no stamper)
Main Cylinder: 10" bore trunnion design
Main Ram Penetration: Deep penetration into bale chamber
System Pressure: 3000 psi
Main Motor: 50, 75, Twin 50 or Twin 75 HP
Feed Type: Conveyor, loader
Wire Tying: Accent 470;
Plastic strapping optional
Shear: Serrated blade standard (straight blades optional)
Door: Combination bale release and bale separation door
Optional: Hydraulic stamper at the shear
Meets all current ANSI 245.5 Safety Standards

PRODUCTION OPTIONS

12.4 Ton Hydraulic Stamper
Tool steel shear blades: straight ram/serrated beam blades for MSW & NF metals applications
Open operator platform above charge box w/stairs & railing
Operator platform and enclosure with heat & AC
Nema 4 upgrade
Power unit located other than position #1
Accent-Enviro Bale System
Plastic strapper in lieu of standard wire strapper
Power Unit Cover
Increased Cooling Capacity: Recommended for ambient temperatures above 100 Degrees F, Required for ambient temperatures above 110 Degrees F
Panel heaters both panels



BEYOND THE EXPECTED