



PAC Series

For corrugated & packaging trim, shredded material and textiles

Key Advantages:

- Single Tension Cylinder – the side and top channels are hinged –creating four way tension – 3x greater friction force than competitive designs – creating heavier bales
- Best Auto-tie is the industry featuring pull technology, pulling the opposite side wire to the twisting, cutting and knotting process. Tier unit is on castors so you can easily open the unit to inspect and adjust tier for more accurate tying.
- Subfloor System – all units are heavy construction with inner liner system on floor and ram bottoms - provides a much longer lasting design plus much less expensive to renew vs. the competition
- Category III Safety features – all standard



HarrisAmericanCo.com

PAC Series

PRODUCTION OPTIONS

Bale Size: 30" x 43" x variable
Hopper Lengths: 30", 40", 50"
Main Cylinder: 7" or 8" bore trunnion design
System Pressure: 3000 psi (7"), 2500 psi (8")
Main Motor: 30, 50, 75 or Twin 30 HP
Feed Type: Air trim system, conveyor
Meets all current ANSI 245.5 Safety Standards

Dust Pick-Up Hood at Tier Station &
Rear Cylinder (8" Port)
Off-side tier controls
Additional Infrared Photo Eyes
Hopper extension up to 48"
Remote Floor Mounted Power Unit
Water mist (2 nozzle)
Wire Run out Sensors
Increase conveyor controls up to 15HP
Additional 4' Bale Table
Bale Runout Sensor
NEMA 4 upgrade
Textile option with: Rounded Retainer Bar

