



# WB Two Ram

For all recycling grades and NF metals

## Key Advantages:

- Fabricated from heavy structural members and plate, keyed and fitted for proper alignment. Replaceable liner systems featuring 500 Brinell rating, hardest liners in the two ram class.
- Optimal Hydraulic Operating Pressures – 3000-4000 psi, with ram penetration within 8” of the end wall – 82% - for compaction on every stroke and heavier bales
- Dual Motor Power Unit design – providing you redundancy (if one motor down can still operate), power conservation – one motor can go to sleep mode and automatically be brought back into production on demand.
- Manifold Block System – featuring cartridges instead of poppet valves – much easier to replace as well as the power unit runs much quieter, cooler, and much longer lasting
- HMI with 10” Exor eSmart Touch Screen located on the floor for easy access while running in automatic for most grades.
- Category III Safety – all standard



[HarrisAmericanCo.com](http://HarrisAmericanCo.com)

# WB Two Ram Series

Models: W721, W828

Bale Size: 60" x 30" x 45"

Feed Opening: 87" x 60",

110" x 60" (long side-no stamper)

Main Cylinder: 12" bore trunnion design

Main Ram Penetration: Deep penetration into bale chamber

System Pressure: 3000 psi (W721), 3500 psi (W828)

Main Motor: Twin 50, Twin 75 HP,  
or Triple 75 HP (Model W828 only)

Feed Type: Conveyor, loader

Wire Tying: Accent 470 standard; Plastic strapping optional

Shear: Serrated blade standard (straight blades optional)

Door: Combination bale release and bale separation door

Meets all current ANSI 245.5 Safety Standards

## PRODUCTION OPTIONS

18.8 Ton Hydraulic Stamper<sup>1</sup>

Tool steel shear blades: straight ram/serrated beam blades  
for MSW & NF metals applications

Open operator platform above charge box w/stairs & railing

Operator platform and enclosure with heat & AC

Flooded inlet power unit (T75HP & 225HP)

Nema 4 upgrade

Power unit located other than position #1

Accent-Enviro Bale System

Plastic strapper in lieu of standard wire strapper

Power Unit Cover

Increased Cooling Capacity: Recommended for ambient  
temperatures above 100 Degrees F, Required for  
ambient temperatures above 110 Degrees F

Panel heaters both panels



**BEYOND THE EXPECTED**